



Material Safety Data Sheet

For

Dongguan Lizhou Energy Co., Ltd.

Nanmen Industrial Zone, Qiaoli, Changpeng, Dongguan, Guangdong, China

and for their product

Li-Polymer Battery

Model/type reference: 300820, 300930, 381018, 381020, 301030, 301214, 301220, 301230, 301423, 301430, 301535, 301730, 302030, 302323, 303030, 321220, 322030, 303040, 331430, 341355, 350830, 350926, 351025, 351215, 352020, 352030, 352323, 361020, 362929, 371014, 371029, 371114, 381119, 381225, 381230, 381423, 400930, 401019, 401020, 401022, 401025, 401029, 401030, 401035, 401040, 401119, 401120, 401121, 401214, 401215, 401225, 401229, 401230, 401235, 401515, 401623, 401624, 401730, 401737, 402025, 402030, 402530, 403035, 421121, 421130, 421133, 421520, 431220, 450825, 451025, 451215, 451220, 451235, 451423, 451535, 451827, 501015, 501017, 501018, 501020, 501025, 501035, 501119, 501215, 501220, 501225, 501230, 501235, 501240, 501417, 501419, 501423, 501430, 501515, 501630, 502025, 502030, 502535, 502245, 502533, 541035, 541515, 551035, 551115, 551125, 552535, 601215, 601230, 601515, 602020, 602030, 602035, 602530, 602535, 603030, 701128, 701415, 701416, 701417, 702030, 702050, 851721

Preparation Date.....: Jan. 04, 2016

Laboratory: **Shenzhen Better Testing Technology Co., Ltd.**

Address: A311, University Creativity Park, Xilihu Road, Nanshan District, Shenzhen, PRC.

Compiled by (name+ signature) ..: Joe Zhen

Approved by (name+ signature) ..: Apple Li





Section 1- Chemical Product and Company Identification

1. Chemical Product Identification

Product name: Li-Polymer Battery

Model: See page first

2. Company Identification

Manufacturer /Supplier Name: Dongguan Lizhou Energy Co., Ltd.

Address: Nanmen Industrial Zone, Qiaoli, Changpeng, Dongguan, Guangdong, China

Emergency Telephone No.(24h): +86-0750-36111288

This MSDS was prepared by Shenzhen Better Testing Technology Co., Ltd.

Item Number: BTT201511228169MS-1

Referenced documents: ISO 11014:2009 Safety data sheet for chemical products;

Section 2 – Hazards Identification

Preparation hazards and classification	When the battery is In extreme pressure deformation, high-temperature environment, overload, short-circuit condition, or disassemble the battery, an explosion of fire and chemical burn hazards may occur.
Apperance, Color, and Odor	Solid object with no odor, no color.
Primary Route(s) of Exposure	These chemicals are contained in a sealed stainless steel enclosure. Risk of exposure occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, exposure to the electrolyte solution contained within can occur by Inhalation, Ingestion, Eye contact and Skin contact
Potential Health Effects:	<p>ACUTE (short term): see Section 8 for exposure controls In the event that this battery has been ruptured, the electrolyte solution contained within the battery would be corrosive and can cause burns.</p> <p>Inhalation: A battery volatilizes no gas unless it was damaged. Damaged battery will volatilize little gas that may stimulate the respiratory tract or cause an anaphylaxis in serious condition.</p> <p>Ingestion: Swallowing battery will be Damaged to the respiratory tract and Cause chemical burns to the stomach; in serious conditions it will cause Permanent damage.</p> <p>Skin: In normal condition, Contact between the battery and skin will not cause any harms. Contact with a damaged battery may cause skin allergies or chemical burns.</p> <p>Eye: in normal condition, Contact between the battery and eyes will not cause any harms. However, the gas Volatilize from a damaged battery may be harmful to</p>



	eyes. CHRONIC (long term): see Section 11 for additional toxicological data
Medical Conditions Aggravated by Exposure	Not applicable
Reported as carcinogen	Not applicable

Section 3 – Composition/Information on Ingredients

Li-ion Rechargeable Battery Pack is a mixture.

Hazardous Ingredients (Chemical Name)	Concentration or concentration ranges (%)	CAS Number
Aluminum	9.34	7429-90-5
Polycaprolactam(NYLON 6)	1.61	N/A
SBR (CF ₂ -CF ₂) _n	0.86	9003-55-8
Copper	8.94	7440-50-8
Poly Vnylidene Fluoride PVDF(-[CH ₂ -CF ₂]- _n)	8.83	24937-79-9
Lithium Cobaltate	29.34	12190-79-3
lithium hexafluoroarsenate (LiPF ₆)	3.41	21324-40-3
Ethylene carbonate (EC)	6.04	96-49-1
Diethyl carbonate (DEC)	7.12	105-58-8
Propylene carbonate (PC)	1.35	108-32-7
Nickel	1.08	7440-02-0
Graphite powder(C)	21.06	7782-42-5
Carbon balck	0.91	1333-86-4
Polypropylene	2.14	9003-07-0
Polymide Film	0.61	N/A
Polyethylene	1.52	9002-88-4

Note: CAS number is Chemical Abstract Service Registry Number.

N/A=Not apply.

Section 4 – First-aid Measures

Inhalation	If contents of an opened battery are inhaled, remove source of contamination or
-------------------	---



	move victim to fresh air. Obtain medical advice.
Skin contact	If skin contact with contents of an open battery occurs, as quickly as possible remove contaminated clothing, shoes and leather goods. Immediately flush with lukewarm, gently flowing water for at least 30 minutes. If irritation or pain persists, seek medical attention. Completely decontaminate clothing, shoes and leather goods before reuse or discard.
Eye contact	If eye contact with contents of an open battery occurs, immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 30 minutes while holding the eyelids open. Neutral saline solution may be used as soon as it is available. If necessary, continue flushing during transport to emergency care facility. Take care not to rinse contaminated water into the unaffected eye or onto face. Quickly transport victim to an emergency care facility.
Ingestion	If ingestion of contents of an open battery occurs, never give anything by mouth if victim is rapidly losing consciousness, or is unconscious or convulsing. Have victim rinse mouth thoroughly with water. DO NOT INDUCE VOMITING. Have victim drink 60 to 240 mL (2-8 oz.) of water. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Have victim rinse mouth with water again. Quickly transport victim to an emergency care facility.

Section 5 – Fire-fighting Measures

Flammable Properties	In the event that this battery has been ruptured, the electrolyte solution contain within the battery would be flammable. Like any sealed container, battery cells may rupture when exposed to excessive heat; this could result in the release of flammable or corrosive materials.
Suitable extinguishing Media	Use extinguishing media suitable for the materials that are burning.
Unsuitable extinguishing Media	Not available
Explosion Data	Sensitivity to Mechanical Impact: This may result in rupture in extreme cases Sensitivity to Static Discharge: Not Applicable
Specific Hazards arising from the chemical	Fires involving Li-ion Rechargeable Battery Pack an be controlled with water. When water is used, however, hydrogen gas may evolve. In a confined space, hydrogen gas can form an explosive mixture. In this situation, smothering agents are recommended to extinguish the fire
Protective Equipment and precautions for firefighters	As for any fire, evacuate the area and fight the fire from a safe distance. Wear a pressure-demand, self-contained breathing apparatus and full protective gear. Fight fire from a protected location or a safe distance. Use NIOSH/MSHA approved full-face self-contained breathing apparatus (SCBA) with full protective gear.



NFPA	Health: 0 Flammability: 0 Instability: 0
------	--

Section 6 – Accidental Release Measures

Personal Precautions, protective equipment, and emergency procedures	Restrict access to area until completion of clean-up. Do not touch the spilled material. Wear adequate personal protective equipment as indicated in Section 8.
Environmental Precautions	Prevent material from contaminating soil and from entering sewers or waterways.
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.
Methods and materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.

Section 7 – Handling and Storage

Handling	<p>Do not dismantle, open or shred secondary Li-ion Rechargeable Battery Pack;</p> <p>Don't handling Li-ion Rechargeable Battery Pack with metalwork. Do not open, disassemble, crush or burn battery. Ensure good ventilation/ exhaustion at the workplace.</p> <p>Prevent formation of dust.</p> <p>Information about protection against explosions and fires: Keep ignition sources away- Do not smoke.</p>
Storage	<p>If the Li-ion Rechargeable Battery Pack is subject to storage for such a long term as more than 3 months, it is recommended to recharge the Li-ion Rechargeable Battery Pack periodically.</p> <p>3 months: -10°C~+40°C, 45 to 85%RH And recommended at 0°C~+35°C for long period storage.</p> <p>The capacity recovery rate in the delivery state (50% capacity of fully charged) after storage is assumed to be 80% or more.</p> <p>The voltage for a long time storage shall be</p>



	<p>3.7V~4.2V range.</p> <p>Do not storage Li-ion Rechargeable Battery Pack haphazardly in a box or drawer where they may short-circuit each other or be short-circuited by other metal objects.</p> <p>Keep out of reach of children.</p> <p>Do not expose Li-ion Rechargeable Battery Pack to heat or fire. Avoid storage in direct sunlight.</p> <p>Do not store together with oxidizing and acidic materials.</p>
--	--

Section 8 – Exposure Controls and Personal Protection

Engineering Controls	<p>Use local exhaust ventilation or other engineering controls to control sources of dust, mist, fumes and vapor.</p> <p>Keep away from heat and open flame. Store in a cool, dry place.</p>
Personal Protective Equipment	<p>Respiratory Protection: Not necessary under normal conditions.</p> <p>Skin and body Protection: Not necessary under normal conditions, Wear neoprene or nitrile rubber gloves if handling an open or leaking battery.</p> <p>Hand protection: Wear neoprene or natural rubber material gloves if handling an open or leaking battery.</p> <p>Eye Protection: Not necessary under normal conditions, Wear safety glasses if handling an open or leaking battery.</p>
Other Protective	Equipment Have a safety shower and eye wash fountain readily available in the immediate work area.
Hygiene Measures	<p>Do not eat, drink, or smoke in work area.</p> <p>Maintain good housekeeping.</p>

Section 9 - Physical and Chemical Properties

Physical State	Form: Solid
	Color: White
	Odour: Monotony
Change in condition:	
pH, with indication of the concentration	Not applicable



Melting point/freezing point	Not available.
Boiling Point, initial boiling point and Boiling range:	Not available.
Flash Point	Not available.
Upper/lower flammability or explosive limits	Not available.
Vapor Pressure:	Not applicable
Vapor Density: (Air = 1)	Not applicable
Density/relative density	Not available.
Solubility in Water:	Insoluble
n-octanol/water partition coefficient	Not available.
Auto-ignition temperature	130°C
Decomposition temperature	Not available.
Odour threshold	Not available.
Evaporation rate	Not available.
Flammability (soil, gas)	Not available.
Viscosity	Not applicable

Section 10 - Stability and Reactivity

Stability	The product is stable under normal conditions.
Conditions to Avoid (e.g. static discharge, shock or vibration)	Do not subject Li-ion Rechargeable Battery Pack to mechanical shock. Vibration encountered during transportation does not cause leakage, fire or explosion. Do not disassemble, crush, short or install with incorrect polarity. Avoid mechanical or electrical abuse.
Incompatible Materials	Not Available
Hazardous Decomposition Products	This material may release toxic fumes if burned or exposed to fire
Possibility of Hazardous Reaction	Not Available

Section 11 - Toxicological Information

Irritation	Risk of irritation occurs only if the cell is mechanically, thermally or electrically abused to the point of compromising the enclosure. If this occurs, irritation to the skin, eyes and respiratory
------------	---



	tract may occur.
Sensitization	Not Available
Neurological Effects	Not Available
Teratoaenicity	Not Available
Reproductive Toxicity	Not Available
Mutagenicity (Genetic Effects)	Not Available
Toxicologically Synergistic Materials	Not Available

Section 12 - Ecological Information

General note:	Water hazard class 1(Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
Anticipated behavior of a chemical product in environment/possible environmental impace/ecotoxicity	Not Available
Mobility in soil	Not Available
Persistence and Degradability	Not Available
Bioaccumulation potential	Not Available
Other Adverse Effects	Not Available

Section 13 – Disposal Considerations

Product disposal recommendation: Observe local, state and federal laws and regulations.

Packaging disposal recommendation: Be aware discarded batteries may cause fire, tape the battery terminals to insulate them. Don't disassembly the battery. Completely discharge containers (no tear drops, no powder rest, scraped carefully). Containers may be recycled or re-used. Observe local, state and federal laws and regulations.

The potential effects on the environment and human health of the substances used in batteries and accumulators; the desirability of not disposing of waste batteries and accumulators as unsorted municipal waste and of participating in their separate collection so as to facilitate treatment and recycling;

Section 14 – Transport Information

This report applies to by sea, by air and by land;

Polymer Li-ion Rechargeable Battery Pack complies with the UN Recommendations on the



Transport of Dangerous Goods; IATA Dangerous Goods regulations, and applicable U.S. DOT regulations for the safe transport of Polymer Li-ion Rechargeable Battery Pack. Batteries containing these cells should be transported as Class 9 hazardous material, except for those battery types declared to be exempt (contact Concorde for a current listing of exempt batteries) and/or The Polymer Li-ion Rechargeable Battery Pack (model: See page first) tested according to the requirements of the UN manual of tests and Criteria, Part III, subsection 38.3;



The Polymer Li-ion Rechargeable Battery Pack according to Section II/Section IB of PACKING INSTRUCTION 965, or Section II of PACKING INSTRUCTION 966~967 of the 2014 IATA Dangerous Goods regulations 55th Edition may be transported. and applicable U.S. DOT regulations for the safe transport of Polymer Li-ion Rechargeable Battery Pack.

The packaging shall be adequate to avoid mechanical damage during transport, handling and stacking. The materials and pack design shall be chosen so as to prevent the development of unintentional electrical conduction, corrosion of the terminals and ingress of moisture.

The package must be handled with care and that a flammability hazard exists if the package is damaged;

Each package must be labeled with a Polymer Li-ion Rechargeable Battery Pack handling label or in addition to the Class 9 hazard label.

The following information is provided for domestic and international transport.

DOT regulations:		
UN Classification (Transport Hazard class):	Class 9-Micellaneous Dangerous Goods;	
UN number:	3480 or 3481	
Packing group:	II	
UN Proper shipping name(technical name):	Lithium ion batteries or Lithium ion batteries contained in equipment or Lithium ion batteries packed with equipment;	
Marine pollutant(Y/N)	N	
Label:	9	
Land transport ADR/RID (cross-broder):		
ADR/RID class:	Class 9-Micellaneous Dangerous Goods and articles	
Danger code(Kemler):	9	
UN-Number:	3480 or 3481	
Packaging group:	II	



Marine pollutant(Y/N):	N	
Label:	9	
Description of goods:	Lithium ion batteries or Lithium ion batteries contained in equipment or Lithium ion batteries packed with equipment;	
Sea transport IMDG:		
IMDG Class:	Class 9-Micellaneous Dangerous Goods;	
UN Number:	3480 or 3481	
Label:	9	
Packaging group:	II	
EMS Number:	F-A, S-I	
Marine pollutant(Y/N):	Y	
Special regulate:	IMDG 188, 230, 310, 348, 957	
Propper shipping name:	Lithium ion batteries or Lithium ion batteries contained in equipment or Lithium ion batteries packed with equipment;	
Air transport ICAO-TI and IATA-DGR:		
UN/ID Number:	3480 or 3481	
Label:	9	
Packaging group:	II	
Marine pollutant(Y/N):	N	
Propper shipping name:	Lithium ion batteries or Lithium ion batteries contained in equipment or Lithium ion batteries packed with equipment;	

